

## **Electric Cutter**



- Quick and simple to operate with minimal effort
- High precision cut every time
- 2 models, up to 25mm or up to 50mm thick material
- Electric operation, a unique feature
- 7 times the torque of conventional pneumatic cutters
- Suitable for rubber with a hardness of 25° Shore A and upwards
- CE approved
- Configurable for right or left handed operation

## **Technical specifications:**

Туре	E0020	E0021
Housing	all Stainless Steel	all Stainless Steel
Knife	Ø 170mm	Ø 225mm
Knife quality	HSS steel	HSS steel
Motor	110 V. 580 W, reversible,	110 V. 750 W, reversible,
	Hitachi	Metabo
Speed motor	variable, 0 – 2.900 RPM	variable, 0 – 3.000 RPM
Speed knife	variable < 40 RPM	variable < 40 RPM
Torque	approx. 280 Nm, depending the RPM	approx. 340 Nm, depending the RPM
Weight	7 kg	13 kg
Cutting capacity	25 mm maximum	50 mm maximum
Hardness material	from 25° to 90° Shore A	from 25° to 90° Shore A
For materials	conveyor belts, rubber and PU sheets	conveyor belts, rubber and PU sheets

For details of your nearest *Flexco* distributor contact Customer Service

Tel	01274 600 942	
Fax	01274 673 644	
E-mail	sales@flexco.co.uk	